
# Floor Standing LifePo4 Battery

## 51.2**V 314Ah**



### Our NOVA VOLT battery compatible with more than 30 brands inverter worldwide



























































### Product advantages

Warranty: 5-10 years. Professional engineer team support after-sale service.

#### Long cycle life

Using high-quality lithium iron phosphate batteries, the cycle life is more than 6000 times at 80%DOD, and can be used for 15-20 years.



High quality Grade A+ Prismatic LiFePO4 battery Higher capacity, higher current, longer life

#### Low internal resistance and high current

Low internal resistance of the battery, excellent continuous high current discharge performance



### Intelligent BMS battery protection

Built-in intelligent BMS (battery management system), effectively avoiding overcharge, overdischarge, overcurrent, short-circuit, balance and other problems.



#### Communicated with multiple brands inverter

Battery BMS supports simultaneous communication and docking with multiple brands inverter

#### Good safety performance

Extreme safety test, no fire, no explosion, no leakage

## 51.2V 314AH

## Floor Standing LifePo4 Battery

## Key Features

- ★ A Grade high quality prismatic cells.
- ★ High quality smart BMS.
- ★ Maintenance free & Low self discharge & Fast and efficient charging.
- ★ LCD Display for intelligent control and monitor.

### Protection

- ★ Over charge detection function
- ★ Over discharge detection function
- ★ Over current detection function
- ★ Temperature protection function
- ★ Short circuit detection function
- ★ Balance function
- ★ Upper computer software monitor


### **Parameters**


Product model	
Product specification	51.2V 314Ah
Nominal voltage	51.2V
Nominal capacity	314Ah
Cell type	LFP
Standard charge voltage	57.6±0.1V
Standard charge current	≤120A
Max charge current	150A
Discharge cut-off voltage	44.8V
Max discharge current	150A
Parallels function	Support 15 units in parallels
Communication interface	RS485,CAN(Optional)
Cycle life	≥6000 Cycles (80%DOD)
Charge temperature range	0~60
Discharge temperature range	-20 ~ 60
Colour	Grey
Dimensions	832*500*250MM
Weight	122Kg
Installation method	Floor Standing

# Floor Standing LifePo4 Battery

### Charging and Discharge curve


Charge and discharge curve @0.5C 25°C






### Cycle Life Curve

Different discharge depth life curves @ 25°C 0.5C



Different discharge depth life curves @ 40°C 0.5C



Charge current

## 51.2V 314AH

# Floor Standing LifePo4 Battery

